

INSTALLATION NOTES:

- 1) TYPICAL PIN/STAPLE INSTALLATION PATTERN SHOWN
- 2) ADD PINS/STAPLES AS NEEDED TO PROVIDE INTIMATE CONTACT OF GRASSGUARD WITH GRADE.
- 3) PINS/STAPLES TO BE INSTALLED FLUSH WITH GRADE.
- 4) FILL SHALLOW DEPRESSIONS WITH FREE DRAINING (NON-CLAY) FILL PRIOR TO INSTALLATION OF GRASSGUARD.
- 5) WEAK AND/OR SATURATED SOILS MAY REQUIRE DRAINAGE IMPROVEMENT AND OR STABILIZATION PRIOR TO INSTALLATION.
- 6) SURFACE MUST BE REASONABLE LEVEL, FIRM AND FREE DRAINING.
- IT IS NOT ADVISABLE TO FILL OR COVER GRASSGUARD WITH SOIL.
- 8) AS ROLLED PRODUCTS TEND TO HAVE "MEMORY", IT IS ADVISABLE TO UNROLL GRASSGUARD AND ALLOW AT LEAT ONE HOUR (OR MORE IN COLD CLIMATES) FOR THE MATERIAL TO REGAIN ITS NATURAL ELAT SHAPE.

9) DUE TO THE MANUFACTURING PROCESS, ONE SIDE OF GRASSCUARD WILL BE MORE ROUGH (COARSE.) THE SURFACE MUST BE INSPECTED PRIOR TO INSTALLATION TO VERIFY THE ROUGH SIDE IS INSTALLED FACE UP.

10) OPTIMUM PERFORMANCE IS OBTAINED BY RESTRICTING VEHICULAR ACCESS UNTIL: A) GRASS HAS GROWN COMPLETELY AND EVENLY

A) GRASS HAS GROWN COMPLETELY AND EVENLY THROUGH THE GRASSGUARD.
B) GRASSGUARD HAS BEEN MOWED AT LEAST TWO TIMES.

11) PRIOR TO FUIL VEGETATED MATURITY, GRASSGUARD STRONGLY RECOMMENDS THAT ACCESSIBILITY BE DISCOURAGED OR DENIED, AND APPROPRIATE SLIP-HAZARD WARNING SIGNAGE BE ERECTED.

12) PIN AND STAPLE OPTIONS:
A) 6" X 1" X 6" U-SHAPED STAPLE
B) 8" X 1" X 8" U-SHAPED STAPLE
C) 12" PIN WITH WASHER

13) INSTALLATION IS RECOMMENDED IN THE APPROPRIATE DIRECTION TO ALLOW TRAFFIC TO FLOW PARALLEL TO GRASSGUARD JOINTS.

NOT TO SCALE



510 O'NEAL LANE EXT BATON ROUGE LA 70819 800 848 4500 www.ind-fab.com OPTIONAL CONCRETE PARKING BUMPERS CAN BE USED TO DELINEATE PARKING SPACES. THEY CAN BE INSTALLED DIRECTIV ONTO THE GRASSGUARD OR JUST BEYOND THE LIMITE.

TYPICAL GRASSGUARD INSTALLATION DETAIL WITH IRRIGATION RECOMMENDATIONS

NOTE PARKING STALL AND DRIVE ISLE DIMENSIONS PER LOCAL CODE

DISCLAMMER:

DISCLAMMER:

THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED BY INDUSTRIAL FABRICS, INC. AND TO THE

BEST OF OUR NATOWLEDGE, ACCUPANTELY REPRESENTS THE GRASSGUARD PRODUCT USE IN THE

BEST OF OUR NATOWLEDGE, ACCUPANTELY FIRAL DETERMINATION OF THE SUITABILITY FOR THE USE

CONTENEDATED AND ITS MANNER OF USE ARE THE SOLE RESPONSIBILITY OF THE USER. CIVIL,

GEOTE CHNICAL AND HYDRAULIC DESIGN AND ANALYSIS SHALL BE PERFORMED BY A QUALIFED ENGINEER.

THIS DRAWING IS BEING FURNISHED FOR CONVENIENCE OF THE USER. ANY PARTY ACCEPTING THIS DOCUMENT DOES SO IN COMPRENED AND AGREES THAT IT SHALL NOT BE DUPLICATED IN WHOLE OR PART, NORD ISCOCASED TO OTHERS WITHOUT THE CONSERT OF INDUSTRIAL PARIETS, OF

NOT FOR CONSTRUCTION

Grass Reinforcement Mesh

TYPICAL SURFACE REINFORCEMENT INSTALLATION DETAIL WITH IRRIGATION RECOMMENDATION