

- 1) TYPICAL PIN/STAPLE INSTALLATION PATTERN SHOWN.
- CONTACT OF GRASSGUARD WITH GRADE.
- 3) PINS/STAPLES TO BE INSTALLED FLUSH WITH GRADE.
- (NON-CLAY) FILL PRIOR TO INSTALLATION OF GRASSGUARD.
- 5) WEAK AND/OR SATURATED SOILS MAY REQUIRE DRAINAGE IMPROVEMENT AND OR STABILIZATION PRIOR TO
- 6) SURFACE MUST BE REASONABLE LEVEL, FIRM AND FREE
- 7) IT IS NOT ADVISABLE TO FILL OR COVER GRASSGUARD WITH
- 8) AS ROLLED PRODUCTS TEND TO HAVE "MEMORY", IT IS ADVISABLE TO UNROLL GRASSGUARD AND ALLOW AT LEAST ONE HOUR (OR MORE IN COLD CLIMATES) FOR THE MATERIAL
- GRASSGUARD WILL BE MORE ROUGH (COARSE.) THE SURFACE MUST BE INSPECTED PRIOR TO INSTALLATION TO VERIFY THE
- - A) GRASS HAS GROWN COMPLETELY AND EVENLY
 - B) GRASSGUARD HAS BEEN MOWED AT LEAST TWO
- 11) PRIOR TO FULL VEGETATED MATURITY, GRASSGUARD STRONGLY RECOMMENDS THAT ACCESSIBILITY BE DISCOURAGED OR DENIED, AND APPROPRIATE SLIP-HAZARD
- A) 6" X 1" X 6" U-SHAPED STAPLE B) 8" X 1" X 8" U-SHAPED STAPLE
- DIRECTION TO ALLOW TRAFFIC TO FLOW PARALLEL TO

NOT TO SCALE



510 O'NEAL LANE EXT **BATON ROUGE LA 70819** 800 848 4500 www.ind-fab.com

THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED BY INDUSTRIAL FABRICS. INC. AND TO THE BEST OF OUR KNOWLEDGE, ACCURATELY REPRESENTS THE GRASSGUARD PRODUCT USE IN THE APPLICATIONS WHICH ARE ILLUSTRATED. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND ITS MANNER OF USE ARE THE SOLE RESPONSIBILITY OF THE USER. CIVIL GEOTECHNICAL AND HYDRAULIC DESIGN AND ANALYSIS SHALL BE PERFORMED BY A QUALIFIED ENGINEER.

THIS DRAWING IS BEING FURNISHED FOR CONVENIENCE OF THE USER. ANY PARTY ACCEPTING THIS DOCUMENT DOES SO IN CONFIDENCE AND AGRESTHAT IT SHALL NOT BE DUPLICATED IN WHOLE OR PART, NOR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF INDUSTRIAL FABRICS, INC.

NOT FOR CONSTRUCTION

GrassGuard **Grass Reinforcement Mesh**

TYPICAL SURFACE REINFORCEMENT INSTALLATION DETAIL WITH IRRIGATION RECOMMENDATION